

SCORPION 6" Android

SCORPION 
RUGGED TABLET & HANDHELD SOLUTIONS

INDUSTRIAL RUGGED HANDHELD WITH 6.0-INCH IPS DISPLAY (15.24CM)

- MT8735B Cortex-A53 CPU
- IP67 (protected against dirt and temporary submersion)
- Fall protection from up to 1.5 meters height
- 1D/2D barcode reader (tilted 25°)
- Long-term availability



SYSTEM

CPU	Qualcomm MT8735B Quad-Core Cortex-A53, 1.45GHz
Graphics Card	Intel® HD Graphics (Gen 7)
Operating System	Android 10
RAM	4GB
Storage Capacity	64GB

DISPLAY / TOUCH

Display Size	6.0" (15.24cm)
Resolution	1280x720
Touch Screen	5-point capacitive (Corning Gorilla Glass 3)
Brightness	430 cd/m ²

COMMUNICATION

WLAN	802.11 b/g/n/ac (2.4GHz + 5.8GHz dual band Wi-Fi)
Bluetooth	Bluetooth 4.0 (BLE) class 1
GPS	yes
WWAN	LTE
NFC	13.56MHz support: ISO 14443A/14443B/15693/18092/Mifare

INTERFACE

USB	1x USB-C
Audio	1x speaker + 1x 3,5mm audio-out
SIM Slot	1x micro SIM
Expansion	1x micro SD

EQUIPMENT

Barcode Reader	1D/2D (included)
Camera	2 MP (front) / 8MP (rear)
Battery	5,000 mAh, 3.7 Volt
Power Supply	DC 100 ~ 240V, 50/60Hz, output 5V/2.5A

OTHER

Operating Temperature	-10° ~ 50°C
Protection Class	IP67 + MIL-STD-810G
Dimensions	185 x 93 x 20.7mm
Weight	380g

SCORPION 6" Android

SCORPION 
RUGGED TABLET & HANDHELD SOLUTIONS

ACCESSORIES AND OPTIONS

Dual Docking (22601)	Battery charging device for Scorpion 6" enables (simultaneous) charging of up to two handhelds compact and easy-to-use
Single Dockingstation (24587)	Battery charging device for Scorpion 6" enables charging of one 6" handheld compact and easy-to-use
Replacement Battery (24610)	5.000 mAh, 3.7 Volt
Pistol Grip (24543)	Pistol grip with trigger for easier scanning of 1D or 2D barcodes
Touch Pen (24999)	Touch pen for intuitive device interactions and improved usability

DUAL DOCKING



PISTOL GRIP



SCORPION 6" - Scope of supplies

1x SCORPION 6" - Android - Rugged Handheld Terminal

1x hand strap

1x EU power adapter USB 5V/2A

1x USB charging cable (USB-C Male to USB A-Male)

1x USB OTG cable (USB-C Male to USB A-Female)